



bolted bonnet, gland seal
rising stem, loose plug/spring

Connection:

flanges acc. to DIN PN10/16

Body: nodular cast iron

Inner parts: gunmetal

Seat sealing: metallic

temperature range: $-10^{\circ}\text{C} - 225^{\circ}\text{C}$

DN	PN	L	H	$\varnothing d$	$\varnothing D$	$\varnothing k$	$n \times \varnothing d1$	kg			
15	16	130	189	120	95	65	4 x 14	3,9			
20	16	150	189	120	105	75	4 x 14	4,3			
25	16	160	203	140	115	85	4 x 14	5,4			
32	16	180	203	140	140	100	4 x 18	7,0			
40	16	200	246	160	150	110	4 x 18	9,5			
50	16	230	254	160	165	125	4 x 18	12,9			
65	16	290	293	180	185	145	4 x 18	18,4			
80	16	310	322	200	200	160	8 x 18	24,5			
100	16	350	381	225	220	180	8 x 18	36,0			
125	16	400	427	250	250	210	8 x 18	56,0			
150	16	480	521	400	285	240	8 x 22	78,0			
200	10	600	643	520	340	295	8 x 22	122,0			
200	16	600	643	520	340	295	12 x 22	122,0			
250	10	730	780	520	395	350	12 x 22	247,0			
250	16	730	780	520	395	350	12 x 26	247,0			
300	10	850	890	520	445	400	12 x 22	336,0			
300	16	850	890	520	445	400	12 x 26	336,0			